

Midget 35mm Full Frame with Exposure Automation

PETRI
Color 35E
MINI MATE



Even smaller and lighter than conventional half frame cameras. Weighs only $13\frac{3}{4}$ oz. Measures only 4 in. long. This new 35mm full frame Electric Eye camera is designed so that the lens retracts into the camera body. Extremely convenient to carry. Comfortably slips into pocket or handbag. Of course, outdoors during the day or indoors at night, color photography is a snap. Just press the shutter button. Every shot will be satisfactory for you.

Buy one and make it your 'Mini Mate'!!



BIG FEATURES IN SMALL BODY

The thinner and smarter camera—— 'MINI MATE' with Snap-out lens.

So easy to extend the lens. And, so easy to retract it. Both by one action of your finger tips. While the lens is being retracted, a red warning filter obstructs viewing to signal shooting without extending the lens.



COMPLETE CdS EXPOSURE AUTOMATION

Exposure is automatically adjusted by the Electric Eye system. A sensitive CdS exposure meter catches the light entering the lens and makes all adjustments for correct exposure control. Even when you add filters, the exposure meter performs perfectly.

The built-in exposure meter also lets you know of poor lighting conditions. If the light is insufficient, the red warning filter appears in the viewfinder and tells you to switch to flash photography.

AUTOMATIC FLASH SETTING

Shooting with flash is extremely simple, you only set the guide number. Then, the shutter is automatically set at 1/30 sec. and the Camera works out the right size of diaphragm opening. No complicated calculation is required.

MAJOR SPECIFICATION

TYPE: Automatic 35mm. camera with built-in "Electric Eye" CdS exposure meter.

FILM: 35mm. film in color or black and white.

PICTURE: 24mm.×36mm.

LENS: Petri 40mm. f/2.8, 4 elements in 3 groups.

VIEWFINDER: Bright line frame with parallax correction marks, warning signals for improper exposure conditions and lens retraction.

FOCUSING: Front lens ring rotating system. Focusing scale and zone symbols available. The lens mount retracts into the camera body.

EXPOSURE SYSTEM: Super sensitive "Electric Eye" CdS exposure meter, EV ranging 8 to 16.7 with ASA 100 (DIN 21) film.

BATTERY TESTER: Incorporated for checking the adequacy of a 1.3 volt mercury battery for the exposure meter.

SHUTTER: Petri programming shutter, 1/30 sec. to 1/200 sec. The cable release socket available.

SYNCHRONIZATION: Automatic flash setting with X synchronization.

FILM TRANSPORT: Single stroke movement (130° drive), double exposure prevention.

FILTER SIZE: 40.5mm. screw-in type.

LENS HOOD: Exclusive lens hood.

DIMENSIONS: 4.0×2.6×1.8 in. (101×64×48mm.)

WEIGHT: 13¾ oz. (390 gr.)

OTHER OUTSTANDING FEATURES

This tiny camera has all the important features you would expect in an easy-to-operate 35mm full frame camera.

EASY FOCUSING

Zone focusing system enables easy and fast focusing. The critical sharpness of the lens and its great depth-of-field range combine to compensate for slight mistakes in focusing. Distance scale also available.

CORDLESS FLASH CONTACT

If you use a cordless flash unit such as Petri Flashgun, simply slip the foot of the unit into the accessory shoe, and it automatically makes contact with the shutter mechanism.

The camera also has a flash socket for an ordinary flash unit.

SIMPLE LOADING SYSTEM

Petri's unique system accepts any standard 35mm film and prevents film from slipping out of the take-up spool.

PETRI CAMERA COMPANY, INC.

PETRI CAMERA N.V.

PETRI INTERNATIONAL (USA) CORP.
(WEST COAST SERVICE STATION)

PETRI CAMERA CORP. OF OKINAWA

25-12, Umeda 7-Chome, Adachi-ku, Tokyo, Japan

Freeport Building, Schiphol Centrum, Holland

432 Park Ave. South, New York, N.Y. 10016, U.S.A.

7407 ½ Melrose Ave., Los Angeles, Calif. 90046, U.S.A.

1-25 Matsushita-Cho, Naha, Okinawa

