



Battery Characterization for ThermoChron® DS1922L

The battery lifetime of the ThermoChron® is factor of sample rate and operating temperature. The following charts present the expected lifetime.

Battery Lifetime vs Temperature at slow sample rates (standard resolution)




Battery Lifetime vs Temperature at slow sample rates (high resolution)




Tv. Venceslau de Morais, 4-1B
2400-260 Leiria · PORTUGAL
T +351 244 852 222
F +351 244 852 221
www.eclo.pt | info@eclo.pt

Battery Lifetime vs Temperature at fast sample rates (standard resolution)




Battery Lifetime vs Temperature at fast sample rates (high resolution)




Tv. Venceslau de Morais, 4-1B
 2400-260 Leiria · PORTUGAL
 T +351 244 852 222
 F +351 244 852 221
www.eclo.pt | info@eclo.pt

Battery Lifetime vs Different Sample Rates (standard resolution)



Battery Lifetime vs Different Sample Rates (high resolution)



FOR DETAILED INFORMATION ABOUT
OUR PRODUCTS AND SERVICES, PLEASE
VISIT US AT:

WWW.ECLO.PT

Product names may be registered trade marks of their respective owners. All information is correct at the time of printing. Eclo reserves the right to make any changes, corrections or improve his products and specifications without prior notification, especially when dictated by supplier originated modifications. Eclo does not assume any responsibility for the use of the described product neither does warrant nor represent that any license, either express or implied, is granted under any Eclo patent right, copyright, or other intellectual property. ©Eclo, Lda.



Tv. Venceslau de Morais, 4-1B
2400-260 Leiria · PORTUGAL
T +351 244 852 222
F +351 244 852 221
www.eclo.pt | info@eclo.pt